Amendment to the Claims

What is claimed is:

1 - 38 (canceled)

39. (currently amended) A method for culturing cells in a reaction system comprising a container for dialysis fluid, a membrane module and a culture vessel for culturing cells, the method comprising:

using [[a]] the membrane module in fluid communication with the container and the <u>culture vessel</u> space for culturing cells, the module including at least two-spaces a dialysis fluid space and a culture fluid space separated by a membrane, the membrane functioning as a dialysis membrane;

circulating a dialysis fluid through the container and the dialysis fluid space of the membrane module one of the at least two module spaces;

circulating a culture fluid containing cells through the culture vessel and the culture fluid space of the membrane module the other of the at least two module spaces;

introducing a first gas into the culture fluid in the culture vessel space for culturing the cells; and

introducing a second gas into the culture fluid in the culture fluid space in the membrane module.

- 40. (previously presented) The method of claim 39, wherein introducing the second gas includes passing gas directly into the culture fluid present in the membrane module.
- 41. (previously presented) The method of claim 39, wherein introducing the second gas includes passing gas indirectly into the culture fluid present in the membrane module.

JAN. 30. 2006 1:49PM AVENTIS US PAT DEPT

NO. 1506 P. 5

- 42. (previously presented) The method of claim 41, wherein passing gas indirectly includes introducing the second gas into the dialysis fluid in the container for dialysis fluid, wherein the gas passes to the culture fluid present in the membrane module via the membrane of the membrane module.
- 43. (previously presented) The method of claim 40, wherein gas is introduced both directly and indirectly at the same time.
- 44. (previously presented) The method of claim 41, wherein gas is introduced both directly and indirectly at the same time.
- 45. (currently amended) The method of claim 39, including using a membrane module that includes at least one gas supplying means and further comprising directly introducing the second gas into the dialysis fluid space or the culture fluid space or both supplying at least one of the at least two spaces with the second gas via the gas supplying means.
- 46. (previously presented) The method of claim 45, wherein supplying the second gas includes supplying the gas through an outlet located in the membrane module space carrying the culture fluid.
- 47. (previously presented) The method of claim 45, wherein supplying the second gas includes supplying the gas through a tube.
- 48. (previously presented) The method of claim 45, wherein the supplying the second gas includes supplying the gas through a nozzle outlet.
- 49. (previously presented) The method of claim 39, including using a membrane comprising a material selected from the group comprising regenerated cellulose, polyamide, polypropylene and polysulforte.

JAN. 30. 2006 1:49PM AVENTIS US PAT DEPT NO. 1506 P. 6

50. (previously presented) The method of claim 39, including using a membrane module that is a plate module

51. (Canceled).

- 52. (previously presented) The method of claim 39, wherein the membrane is formed of Cuprophan.
- 53. (previously presented) The method of claim 39, wherein using the membrane module includes selecting a membrane module that provides sufficient gas exchange for the cells.
- 54. (previously presented) The method of claim 53, wherein selecting a membrane module that provides sufficient gas exchange includes selecting a membrane module having an adequate area/volume ratio and an adequate gas permeability coefficient.
- 55. (previously presented) The method of claim 54, wherein selecting a membrane module that provides sufficient gas exchange includes selecting a membrane module having an area/volume ratio of at least about 5 m² per liter.
- 56. (previously presented) The method of claim 55, wherein selecting a membrane module that provides sufficient gas exchange includes selecting a membrane module having an area/volume ratio of at least about 10 m² per liter.
- 57. (previously presented) The method of claim 56, wherein selecting a membrane module that provides sufficient gas exchange includes selecting a membrane module having an area/volume ratio of at least about 13 m² per liter.
- 58. (previously presented) The method of claim 54, wherein selecting a membrane module that provides sufficient gas exchange includes selecting a

JAN. 30. 2006 1:50PM AVENTIS US PAT DEPT NO. 1506 P. 7

membrane module having an oxygen permeability coefficient equal to or greater than about 0.066 cm per minute.

59. (previously presented) The method of claim 39, wherein the container for dialysis fluid includes at least one of a means for supplying gas and a means for removing gas.

- 60. (previously presented) The method of claim 39, further comprising increasing the pressure in at least one of the membrane module, the space for culturing the cells, and the container for dialysis fluid.
- 61. (previously presented) The method of claim 39, wherein supplying the first gas includes individually and independently selecting the first gas from the group consisting of air, oxygen, nitrogen, carbon dioxide and mixtures thereof.
- 62. (previously presented) The method of claim 61, wherein supplying the second gas includes individually and independently selecting the second gas from the group consisting of air, oxygen, nitrogen, carbon dioxide and mixtures thereof.
- 63. (previously presented) The method of claim 62, wherein the second gas is oxygen.
- 64. (previously presented) The method of claim 62, wherein the second gas is carbon dioxide.
- 65. (previously presented) The method of claim 39, wherein the cells are selected from the group comprising microbial cells, fungal cells, animal cells, and plant cells.
- 66. (previously presented) The method of claim 65, wherein the cells are Escherichia coli cells.

JAN. 30. 2006 1:50PM AVENTIS US PAT DEPT

- 67. (previously presented) The method of claim 39, further comprising sterilizing the reaction system.
- 68. (previously presented) The method of claim 67, further comprising inoculating the culture vessel with cells to be cultured subsequent to sterilizing the reaction system.
- 69. (previously presented) The method of claim 39, further comprising harvesting cultured cells.
 - 70. (currently amended) A membrane module comprising:

at least two spaces separated by a membrane, wherein one space is a dialysis fluid space, the other space is a culture fluid space and the membrane is a dialysis membrane having internal spaces a liquid flows through each space, the liquid in one of the at least two spaces being dialysis fluid and the liquid in the other of the at least two spaces being culture fluid; and

at least one gas supplying means, the gas supplying means having an outlet and being located in one of the <u>internal</u> spaces.

71 - 80. (canceled)

81. (currently amended) A method for culturing cells in a reaction system comprising a container for dialysis fluid, a membrane module and a culture vessel for culturing cells, the method comprising:

using a membrane module according to claim 70, wherein the membrane module is in fluid communication with the container and the vessel for culturing cells, the module including at least two spaces separated by a membrane, the membrane functioning as a dialysis membrane;

circulating a dialysis fluid through one of the at least two module spaces;

circulating a culture fluid containing cells through the other of the at least two module spaces;

introducing a first gas into the culture fluid in the space for culturing the cells; and introducing a second gas into the culture fluid in the membrane module.

- 82. (currently amended) A reaction system for culturing cells, comprising:
 - a container for dialysis fluid;
 - a culture vessel for culturing cells; and

at least one membrane module inserted in between the container and the culture vessel, wherein the membrane module comprises at least two spaces separated by a <u>dialysis</u> membrane, wherein a liquid flows through each space, the liquid in one of the at least two spaces being dialysis fluid and the liquid in the other of the at least two spaces being culture fluid, and the membrane module further includes at least one gas supplying means, the gas supplying means having an outlet and being located in one of the spaces.

- 83. (Canceled)
- 84. (previously presented) The reaction system of claim 82, wherein the container for dialysis fluid contains at least one gas-introducing device.
- 85. (previously presented) The reaction system of claim 82, wherein a membrane of the membrane module has a gas perineability coefficient sufficient to ensure sufficient gas supply during passage of the culture fluid through the membrane module.
- 86. (previously presented) The reaction system of claim 82, wherein a membrane of the membrane module has a gas permeability coefficient sufficient to ensure sufficient gas exchange in the culture fluid located in the membrane module.
- 87. (previously presented) The reaction system of claim 82, wherein a membrane of the membrane module has an area/volume ratio sufficient to ensure

adequate gas supply during passage of the culture fluid through the membrane module.

- 88. (previously presented) The reaction system of claim 82, wherein a membrane of the membrane module has an area/volume ratio sufficient to ensure adequate gas exchange in the culture fluid located in the membrane module.
- 89. (previously presented) The reaction system of claim 82, wherein the membrane module has an area/volume ratio of at least about 5 m² per liter.
- 90. (currently amended) The reaction system of claim 89, wherein the area/volume ration ratio of the membrane module is at least about 10 m² per liter.
- 91. (previously presented) The reaction system of claim 90, wherein the area/volume ratio of the membrane module is at least about 13 m² per liter.
- 92. (previously presented) The reaction system of claim 82, wherein the membrane module has an oxygen permeability coefficient equal to or greater than 0,066 cm per minute.